

**PRODUCT DATA SHEET
POPULAR PVA**

<u>PRODUCT NAME:</u>	POPULAR PVA PAINT
<u>PRODUCT BRAND:</u>	SUPREME
<u>FINISH:</u>	MATT
<u>COLOUR:</u>	WHITE AND PASTEL TINTS
<u>VEHICLE TYPE:</u>	ACRYLIC EMULSION
<u>PIGMENT TYPE:</u>	ORGANIC AND INORGANIC OXIDES
<u>SOLVENT TYPE:</u>	WATER
<u>SPECIFIC GRAVITY:</u>	1.356 AT 25°C
<u>SOLIDS CONTENT:</u>	50 – 55% BY WEIGHT
<u>VISCOSITY AT 25°C:</u>	2200 - 2500 cPu
<u>DRYING TIME:</u>	<u>SURFACE:</u> 30 MINUTES
	<u>HARD:</u> 90 MINUTES TO 2 HOURS
<u>APPLICATION METHOD:</u>	BRUSH OR ROLLER
<u>DESCRIPTION AND FIELDS OF APPLICATION:</u>	A LOW-COST WATERBASED ACRYLIC EMULSION PAINT FOR HOUSEHOLD USE
<u>COVERAGE AT DFT 45 MICRONS:</u>	4 SQUARE METRES PER LITRE
<u>RECOMMENDED DRY FILM THICKNESS:</u>	45 MICRONS MIN PER COAT

DESCRIPTION & GENERAL USE:

A good quality general purpose economy PVA paint for household use. It is recommended that two coats or more be applied, allowing at least four hours between coats. Thinning of the paint is not recommended. All equipment must be cleaned immediately after use with water.

