

## **B & R PRODUCTS (PTY) LTD**

19 Beryllium Rd, Alrode Ext 7, Alberton  
Tel: 011 864-1301 /1302 /1036 /1393  
Fax: 027 11 864-1390  
P.O. Box 1633, Randburg, 2125, South Africa

Reg. No. 80/09849/07  
Email: [bandr@icon.co.za](mailto:bandr@icon.co.za)  
Web: [www.bandr.co.za](http://www.bandr.co.za)

### **PRODUCT DATA SHEET SUPER ACRYLIC PVA**

<b><u>PRODUCT NAME:</u></b>	CONTRACTORSACRYLIC PVA PAINT
<b><u>PRODUCT BRAND:</u></b>	SUPREME
<b><u>FINISH:</u></b>	MATT
<b><u>COLOUR:</u></b>	WHITE AND PASTEL TINTS
<b><u>VEHICLE TYPE:</u></b>	ACRYLIC EMULSION
<b><u>PIGMENT TYPE:</u></b>	INORGANIC OXIDE
<b><u>SOLVENT TYPE:</u></b>	WATER
<b><u>SPECIFIC GRAVITY:</u></b>	1.300 AT 25°C
<b><u>SOLIDS CONTENT:</u></b>	50 – 55% BY WEIGHT
<b><u>VISCOSITY AT 25°C:</u></b>	2200 - 2500 cPu
<b><u>DRYING TIME:</u></b>	<b><u>SURFACE:</u></b> 30 MINUTES
	<b><u>HARD:</u></b> 90 MINUTES TO 2 HOURS
<b><u>APPLICATION METHOD:</u></b>	BRUSH OR ROLLER
<b><u>COVERAGE AT DFT 45 MICRONS:</u></b>	6 SQUARE METRES PER LITRE
<b><u>RECOMMENDED DRY FILM THICKNESS:</u></b>	45 MICRONS MIN PER COAT

#### **DESCRIPTION & GENERAL USE:**

A high quality general purpose acrylic PVA paint for interior and exterior use. It is recommended that two coats be applied, allowing at least four hours between coats. Thinning of the paint is not recommended. All equipment must be cleaned immediately after use with water.

