

**PRODUCT DATA SHEET
WATER-BASED ANTI-CORROSIVE
PRIMER**

<u>PRODUCT NAME:</u>	WATER-BASED ANTI-CORROSIVE PRIMER
<u>PRODUCT BRAND:</u>	SUPREME
<u>FINISH:</u>	MATT
<u>COLOURS:</u>	BLACK AND RED OXIDE
<u>VEHICLE TYPE:</u>	ACRYLIC EMULSION
<u>PIGMENT TYPE:</u>	INORGANIC OXIDES
<u>SOLVENT TYPE:</u>	WATER
<u>SPECIFIC GRAVITY:</u>	1.100 AT 25°C
<u>SOLIDS CONTENT:</u>	40 – 45% BY WEIGHT
<u>VISCOSITY AT 25°C:</u>	25 – 28" FORD CUP 4
<u>DRYING TIME:</u>	<u>SURFACE:</u> 60 MINUTES
	<u>HARD:</u> 24 HOURS
<u>APPLICATION METHOD:</u>	SPRAY OR DIP
<u>COVERAGE AT DFT 35 MICRONS:</u>	5 SQUARE METRES PER LITRE PER COAT
<u>RECOMMENDED DRY FILM THICKNESS:</u>	35 MICRONS

DESCRIPTION & GENERAL USE:

A high quality self-etching anti-corrosive water-based primer for use on bare metal that has been cleaned of dust and grease and/or sandblasted.

The product is ready for use as supplied and requires no thinning.

The primer may be over-coated after a minimum drying time of 24 hours with any conventional industrial or decorative coating.

All equipment must be cleaned immediately after use with water.